

OXOLANE -2,5-DIONE MODIFIED ELECTROSPUN CELLULOSE NANOFIBERS FOR HEAVY METALS ADSORPTION

Musyoka Stephen^a, Ngila Catherine^{a*}, Moodley Brenda^a, Kindness Andrew^a,
Petrik Leslie^b, Greyling Corrine^c

^aUniversity of Kwazulu-Natal, P/Bag X54001, Westville Durban 4000;

^bEnvironmental and Nanoscience Lab, Department of Chemistry, Faculty of Science, University of Western Cape, Private Bag X17, Bellville 7535;

^cCape Organic Chemical Optimization (Pty) Ltd 9 Avenue de Mist, Claremont, 7708, South Africa

ABSTRACT

Keywords: Electrospinning, functionalization, oxolane-2,5-dione, regenerability, nanofibers

Functionalized cellulose nanofibers have been obtained through electrospinning and modification with oxolane-2,5-dione. The application of the nanofibers for adsorption of cadmium and lead ions from model wastewater samples is presented for the first time. Physical and chemical properties of the nanofibers were characterized. Surface chemistry during preparation and functionalization was monitored using Fourier transform-infrared spectroscopy, scanning electron microscopy, carbon-13 solid state nuclear magnetic resonance spectroscopy and Brunauer Emmett and Teller. Enhanced surface area of 13.68 m² g⁻¹ was recorded for the nanofibers as compared to the cellulose fibers with a surface area of 3.22 m² g⁻¹. Freundlich isotherm was found to describe the interactions better than Langmuir: $K_f = 1.0$ and 2.91 mmol g⁻¹; ($r^2 = 0.997$ and 0.988) for lead and cadmium, respectively. Regenerability of the fiber mats have been investigated and the results obtained indicate sustainability in adsorption efficacy of the material.